

Swedish Technical Approval

SC0794-15

and decision on production control, in accordance with chapter 8, 22 and 23 §§ Planning- and Building Act (2010:900), PBL

3M FAST-D 8069E, Splicing Tape

Holder

3M Svenska AB, Bollstanäsvägen 3, 191 89 Sollentuna
Organisation number: 556021-9684
Tel: 08-92 21 00, Fax: 08-92 23 45
E-mail: kundservice@mmm.com, Internet: www.3m.se

Product

3M FAST-D 8069E is an age resistant double-sided jointing tape with acrylate adhesive. Supplied in width from 25 mm upwards.

Intended use

Splicing, installation, joining, and sealing of constructions foils made of polyethylene, intended as water vapour barriers.

Approval

The product satisfy the requirements set forth in chapter 8, 4 § 3, 6 PBL, in respect to and under conditions stated in this certificate, and are therefore approved in accordance with the provisions of the following sections of Boverket Building Regulations (BBR): issued by the National Board of Housing, Building and Planning.

Moisture, General	6:51, first sentence
Air tightness	6:531

The product has been assessed against the Certification Rule CR 031, splice materials for flexible barrier.

Associated documents

“Monteringsanvisning 3M FAST-D 8069E”, dated 160422.

Control

The factory production control (FPC) is monitored by an independent inspection body.
Control agreement: 210-12-0013, Inspection body: SP.

When the building proprietor performs inspection at the building site, he shall check the markings to ensure that the correct products have been supplied and that they are used in accordance with the requirements stated in the approval and the associated document. He must also check that the product is accompanied by a manufacturing assurance, which certifies that the product has been manufactured in accordance with the documents on which this approval is based.



Manufacturer

Production control includes the following sites:
3M, Värnamo and/or 3M Wroclaw

Marking

The product is to be marked at the factory. The marking consists of a label on every product supplied and includes:

Approval holder	3M Svenska AB
Manufacturing site	Wroclaw, Polen
Boverket's registered trademark	†
Certification body and accreditation number	SP Certifiering 1002
Product type designation	3M FAST-D 8069E
Approval number	SC0794-15
Length, Width	value, value
Consecutive manufacture No.	No.
Inspection body	SP

Basis for approval

Report 4F004571, 5F024403-1, and 6F003517 from SP Technical Research Institute of Sweden.

Comments

The tape shall be packed in such a way that it will not be exposed to UV radiation during storage. The durability of the product is deemed to be at least 50 years, provided that it is handled and applied in accordance with the associated documents.

The product has been verified against the following substrates: gypsum plasterboard, spruce structural timber, alkyd and acrylic paint.

Period of validity

This approval is valid until 20 June 2021.

The validity of this approval expires when the characteristics included in this approval shall be CE-marked according to the Construction Products Regulation (EU) 305/2011.

SP Technical Research Institute of Sweden Certification

Håkan Thiman

Linda Ring Thorén