

www.tml.lt

UAB «TML-LT» - Registration code: 302758705
Bijunu st. 19, LT-66226, Druskininkai, Lithuania
www.tml.lt - info@tml.lt - +370 313 41 133

Cable Marker Tube Specification

Part Name : Marker Tubes

Brand : Mark Series (MS)

Size available : 2.0 mm , 2.5 mm , 3.0 mm , 3.2 mm , 3.5 mm , 3.6 mm , 4.0 mm ,
4.2 mm , 4.5 mm , 5.0 mm , 5.5 mm , 6.0 mm , 7.0 mm , 8.0 mm ,
10.0 mm.

Colour : White , Blue , Yellow , Red , Black & Green

Thickness : 0.45 +/- 0.05 mm

Material : PVC (Polyvinyl Chloride)

Standard : Comply to ROHS

Withstand Temperature : 95 c

Tensile Strength At Yield : 12.0 Mpa Test Method : ASTM D 638

Elongation At Yield : 300 % Test Method : ASTM D 638

Colour : Visual Inspection as per approved sample.

Hardness : 80 +/- 5 shore A Test Method : ASTM D2240-97

Volume Resistivity (Ohm.cm) : (10×11) Test Method : ASTM D257

Appearance : Visual Inspection – No abnormality

Flammability Test : Comply to UL 94 V-1

Withstand Voltage : 5000 V – Test Method : JIS C 2410

Printability : The Printing Image will be permanently appear on the tube
As long as the tubes is not expose to excessive heat (not more than 50C)
And touching with chemicals.